

Rotary & Inverter
Compressors

Panasonic



Embrital _____
Hermetic Compressors Distribution in Europe

Panasonic ROTARY COMPRESSOR R134a

Model	Power Source [V/Hz]	Cooling Capacity [W]	COP [W/W]	Displacement [cc/rev]	Weight [Kg]	Outside Diameter / Height [mm]	Accumulator Height / Outside Diameter [mm]	Type
6TS027EAA41	1ph 220-240/50	300	2,34	2,7	3,1	84.0 / 169.0	119.5 / 20.0	Single
6TS035EAA41	1ph 220-240/50	381	2,10	3,5	3,0	84.0 / 169.0	120.1 / 20.0	Single
6TD068EBA41	1ph 220-240/50	690	2,44	6,8	4,0	84.0 / 208.0	135.5 / 20.0	Twin
6SS072EAA41	1ph 220-240/50	795	2,82	7,2	4,8	94.8 / 197.0	133.0 / 20.0	Single
6TD075EAA41	1ph 220-240/50	790	2,36	7,5	4,2	84.0 / 203.0	139.4 / 20.0	Twin
H124C6RECC2	1ph 220-240/50	1.836	4,12	12,4	10,5	110.0 / 277.7	280.7 / 75.0	Single

Panasonic ROTARY COMPRESSOR R410A - HP Application

Model	Power Source [V/Hz]	Cooling Capacity [W]	COP [W/W]	Displacement [cc/rev]	Weight [Kg]	Outside Diameter / Height [mm]	Accumulator Height / Outside Diameter [mm]	Type
H420D5VBAAP2	3ph 380-420/50	9.800	2,95	42,0	24,0	142.6 / 412.0	426.0 / 89.1	Twin

Panasonic ROTARY COMPRESSOR R1234yf (R454C)

Model	Power Source [V/Hz]	Cooling Capacity [W]	COP [W/W]	Displacement [cc/rev]	Weight [Kg]	Outside Diameter / Height [mm]	Accumulator Height / Outside Diameter [mm]	Type
1RS102EAA41	1ph 220-240/50	1.205	2,80	10,2	7,9	110.0 / 252.7	212.7 / 31.75	Single
1RS132EAA41	1ph 220-240/50	1.530	2,94	13,2	9,1	110.0 / 262.7	233.7 / 50.8	Single
1PS192EAA41	1ph 220-240/51	2.140	2,87	19,2	11,5	118.0 / 295.7	267.7 / 54.0	Single
1KS280EAA41	1ph 220-240/50	3.300	3,08	28,0	15,4	132.6 / 338.0	276.4 / 75.0	Single

Rated Test Condition:

Condensing Temperature: 54.4°C

Evaporating Temperature: 7.2°C

Liquid Temperature: 46.1°C

Ambient Temperature: 35.0°C

Suction Temperature: 35.0°C

Panasonic INVERTER ROTARY COMPRESSOR R410A

Model	Power Source [V/Hz]	Cooling Capacity [W] @ 60 rps	COP [W/W]	Displacement [cc/rev]	Weight [Kg]	Outside Diameter / Height [mm]	Accumulator Height / Outside Diameter [mm]	Type	Range [rps]
5SS064ZAA21	1ph DC 220/50	1.600	2,71	6,4	5,5	94.8 / 250.0	253.0 / 64.0	Single	15-120
5SS072ZJC21	1ph DC 220/50	1.770	2,60	7,2	5,3	94.8 / 250.0	275.0 / 65.0	Single	15-120
5SS080ZAB21	1ph DC 220/50	2.000	2,60	8,0	5,9	94.8 / 263.0	280.0 / 64.0	Single	15-120

Rated Test Condition:

Condensing Temperature: 55.0°C

Evaporating Temperature: 7.0°C

Liquid Temperature: 55°C

Ambient Temperature: 35.0°C

Suction Temperature: 18.0°C

Panasonic INVERTER ROTARY COMPRESSOR R32

Model	Power Source [V/Hz]	Cooling Capacity [W] @60 rps	COP [W/W]	Displacement [cc/rev]	Weight [Kg]	Outside Diameter / Height [mm]	Accumulator Height / Outside Diameter [mm]	Type	Range [rps]
9RD132ZAA21	1ph DC 220/50	3.615	2,72	13,2	8,9	110.0 / 301.7	340.7 / 75.0	Twin	15-120
9RD198XAA21	1ph DC 280/50	5.710	2,75	19,8	10,0	111.0 / 327.7	351.7 / 75.0	Twin	15-75
9KD240XCA21	1ph DC 280/50	6.845	2,75	24,0	15,5	132.6 / 365.0	367.0 / 75.0	Twin	15-75
9VD330XAA21	1ph DC 280/50	9.610	2,78	33,0	20,3	142.6 / 427.0	400.0 / 75.0	Twin	15-110
9VD330XBA21	3ph DC 520/50	9.610	2,78	33,0	20,3	142.6 / 427.0	400.0 / 75.0	Twin	15-110
9VD420XAA21	1ph DC 280/50	12.630	3,10	42,0	21,7	142.6 / 442.0	400.0 / 75.0	Twin	15-110
9VD420XBA21	3ph DC 520/50	12.630	3,10	42,0	21,7	142.6 / 442.0	400.0 / 75.0	Twin	15-100

Rated Test Condition:

Condensing Temperature: 55.0°C

Evaporating Temperature: 7.0°C

Liquid Temperature: 55.0°C

Ambient Temperature: 35.0°C

Suction Temperature: 15.0°C

Embrital
Hermetic Compressors Distribution in Europe

Viale Lino Zanussi 8/c
33170 Pordenone (Italy)
Tel. +39 0434 572711
Fax +39 0434 571770
info@embrital.com
www.embrital.com

